



AIR HANDLERS

WITH AMERICAN STANDARD® LINK

MAJOR PRODUCT DIFFERENCES

Supply and return air temperature sensor added.

MODEL NUMBER	CAPACITY (BTU/h)	DIMENSIONS (IN.)			MOTOR TYPE	FILTER SIZE (IN.)
		H	W	D		
TAMXB0A24V21DA	24,000	49.9	17.5	21.8	ECM	16 x 20 x 1
TAMXB0B30V31DA	30,000	55.7	21.3	21.8	ECM	20 x 20 x 1
TAMXB0C36V31DA	36,000	56.9	23.5	21.8	ECM	22 x 20 x 1
TAMXB0C42V41DA	42,000	56.9	23.5	21.8	ECM	22 x 20 x 1
TAMXB0C48V41DA	48,000	61.7	23.5	21.8	ECM	22 x 20 x 1
TAMXB0C60V51DA	60,000	61.7	23.5	21.8	ECM	22 x 20 x 1

WARRANTY

10-year limited warranty on the coil and all other internal functional parts¹

¹ Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at <http://americanstandardair.com> or by phone at 855-260-2975, otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on <http://americanstandardair.com>. Ask your dealer for full warranty information at time of purchase. Warranties are for residential and multi-family use only, some exclusions may apply. Product Registration and Registration Transfer exclusions vary in the US from state to state and in Canada from province to province. To determine if there are specific exclusions for your state or province check your local laws.

APPLICABLE FEATURES IN AMERICAN STANDARD TECHNICIAN APP AND AMERICAN STANDARD DIAGNOSTICS PORTAL

Simple Connection

- TAMX is the next version of the TAM9: Onboard CDA has been removed
- Bluetooth connectivity: Allows connection to the entire system
- 2 generic accessory inputs: Accessory harness included, configuration through the app
- 2 dry-contact output terminals that are configurable
- Supports CAN communicating or 24v systems

Quicker Installation

- Auto-configured airflow
- Auto-configured heat: Resistor included to identify aux heater—heater no longer needs to be configured. Resistor comes with heater kits (hydronic and electric heat).
- Precise superheat control & expansion device diagnostics
- System configuration via app: Also gives the ability to clear error codes on app

Servicing and Quality Reporting

(Available on the American Standard Technician app and portal)

- Delivered CFM: Removes the need for static-to-CFM conversion calculations, helps troubleshoot motor faults or internal errors that lead to no airflow
- ID motor amps: Helps identify errors such as a seized motor
- Evaporator coil temperatures
- Return and supply static pressure (with kit): Provides more diagnostic information to help prevent/diagnose errors with more specific static pressure information